



CSK DC to DC

550W

Antec's new generation CSK DC to DC power supply is crafted for quality, efficiency, and performance. Featuring DC-to-DC architecture, 80 PLUS® BRONZE certification, and quiet 120mm fans, the brand-new CSK DC series includes Antec's solid 5-year warranty. The CircuitShield™ suite of industrial-grade protections ensure that the power delivered to your system is safe and reliable in any environment.



80 PLUS® BRONZE CERTIFIED

Delivering up to 88% efficiency, CSK550 DC to DC utilizes active PFC and gives you a cooler and quieter system, all powered by Continuous Power.

CIRCUITSHIELD™



The full suite of industrial-grade protections includes OCP, OVP, UVP, SCP, OPP, OTP, SIP, and NLO, ensuring the safety and reliability of your power supply in any situation.



5-YEAR WARRANTY

Antec commits a 5-year warranty and offers our quality tech support and customer service.



120MM SILENT FAN

The whisper-quiet 120mm fan provides high airflow with the durability and longevity that is a Antec signature.

THERMAL MANAGER

Thermal Manager, an advanced low voltage fan control for optimal heat & noise management, allows your PSU to stay at the optimal temperature



COMPACT SIZE

Compared to large power supplies on the market, it is smaller in size and can be used with a wider range of computer cases.

CABLES

QTY	Cable Length	Cable Type	Connector(s) Per Cable	Total Connectors
1	600 mm	24(20+4)pin M/B	1	1
1	650 mm (150 mm) / 150 mm	8(4+4)pin CPU	2	2
1	550 mm (150 mm) / 150 mm	8(6+2)pin PCI-E	2	2
2	500 mm (150 mm) / 150 mm	SATA	3	6
1	500 mm (150 mm) / 150 mm	Molex	3	3

CONNECTORS

24-pin M/B Connectors x1	8(4+4)pin CPU Connectors x2	8(6+2)pin PCI-E Connectors x2	SATA Connectors x6	Molex Connectors x3

INPUT

100-240V~, 50Hz-60Hz, 12A Max

OUTPUT

+3.3V	+5V	+12V	-12V	+5VSB
18A	18A	45.8A	0.3A	2.5A
100W		549.6W	3.6W	12.5W
550W				

SPECIFICATIONS

Model	CSK550DC
Safe Model	X5000A533XC-24
Type	ATX 12V 2.52
Dimension	140(L)*150(W)*86(H)
Modular	Non-Modular
Warranty	5 years
Input Voltage	100V-240V
Input Current	12A Max
Input Frequency Range	50Hz-60Hz
PFC	Active PFC
Power Good Signal	100-500ms
Protection	OCP, OVP, UVP, SCP, OPP, OTP, SIP, NLO
Output Capacity	550W
Operation Temperature	0~40°C
Regulatory	cTUVus/TUV/CB/RCM/CE/FCC/BSMI/KC/UKCA/ICES/BIS
Fan	120mm Silent Fan
Certifications	80 Plus Bronze
Connector	1 x 24(20+4)pin MB 2 x 8(4+4)pin CPU 2 x 8(6+2)pin PCI-E 6 x SATA 3 x Molex
Unit Box Dimensions	255mm(L)*195mm(W)*100mm(H)
Shipping Box Dimensions	545mm(L)*425mm(W)*230mm(H)
Net Weight	1.60KG
Gross Weight	1.90KG
UPC#	0-761345-20105-6 CSK550DC US 0-761345-20104-9 CSK550DC JP 0-761345-20103-2 CSK550DC GB 0-761345-20102-5 CSK550DC EC 0-761345-20101-8 CSK550DC AU