

USB-C Cable (M/M) - USB 3.2, Gen 2 (10 Gbps), 5A (100W) Rating, Thunderbolt 3 Compatible, 3 ft. (0.91 m)

MODEL NUMBER: **U420-003-G2-5A**



USB-C cable provides up to 20V 5A (100W) of power—more than enough to charge large-capacity mobile devices, such as the MacBook Pro®. Also connects smartphones, computers, wall chargers and other USB-C devices.

Features

Connects 2 USB-C Devices Power output up to 20V 5A (100W) for fast-charging large mobile devices, such as MacBook Pro Recommended for connecting smartphones, tablets, computers, wall chargers and other USB-C devices Supports USB 3.1 Gen 2 data transfer speeds up to 10 Gbps Backward compatible with previous USB generations Compatible with Thunderbolt 3 devices

Reversible USB-C Male Connectors Fumble-free reversible plugs connect in either direction to ensure fast, easy connection every time

Premium Construction Molded connectors and gold-plated contacts for maximum conductivity and minimum data loss Foil and braid shielding delivers reliable, error-free signal quality and EMI/RFI protection

Specifications

| OVERVIEW | |
|--------------------------|----------------------|
| UPC Code | 037332202888 |
| Technology | Thunderbolt; USB 3.x |
| Cable Type | Passive |
| PHYSICAL | |
| Material of Construction | PVC |
| Cable Jacket Color | Black |

Highlights

- Power output up to 5A for fast-charging large mobile devices
- Supports USB 3.1 Gen 2 data transfer speeds up to 10 Gbps
- Reversible USB-C plugs on both ends for fumble-free connection
- Error-free signal quality and EMI/RFI line noise protection
- Compatible with Thunderbolt™ 3 devices

System Requirements

- Devices with USB-C female connectors

Package Includes

- U420-003-G2-5A USB 3.1 Gen 2 (10 Gbps) Cable with 5A Rating, USB-C to USB-C (M/M), 3 ft.

| | |
|--------------------------------------|-------------------------------------|
| Cable Jacket Rating | VW-1 |
| Cable Outer Diameter (OD) | 5.2MM |
| Cable Length (ft.) | 3 |
| Cable Length (m) | 0.91 |
| Cable Length (in.) | 36 |
| Cable Length (cm) | 91.4 |
| Shipping Dimensions (hwd / in.) | 0.50 x 6.00 x 9.00 |
| Shipping Dimensions (hwd / cm) | 1.27 x 15.24 x 22.86 |
| Shipping Weight (lbs.) | 0.30 |
| Shipping Weight (kg) | 0.14 |
| ENVIRONMENTAL | |
| Operating Temperature Range | 14° to 140°F (-10° to 60°C) |
| Storage Temperature Range | -4° to 185°F (-20° to 85°C) |
| Relative Humidity | 10% to 85% RH, Non-Condensing |
| CONNECTIONS | |
| Side A - Connector 1 | USB C (MALE) |
| Side B - Connector 1 | USB C (MALE) |
| Connector Plating | Nickel |
| Contact Plating | Gold |
| Connector Style | Straight |
| FEATURES & SPECIFICATIONS | |
| USB Specification | USB 3.1 Gen 2 (up to 10 Gbps) |
| STANDARDS & COMPLIANCE | |
| Product Compliance | RoHS; CE (Europe); REACH; FCC (USA) |
| WARRANTY & SUPPORT | |
| Product Warranty Period (Worldwide) | 3-year limited warranty |