



# GaN Charger 65W Retractable Cable

2 x USB-C® PD 65W  
1 x USB-A QC 3.0



## GaN Charger with Retractable Cable

Powerful and compact 65W wall charger, designed to charge up to three devices simultaneously. Equipped with two USB-C® PD 3.0 ports (including one retractable cable) and a USB-A QC 3.0 port, it offers fast and efficient charging for laptops, smartphones, and more.

Integrated GaN technology reduces heat while maximizing efficiency. With USB Power Delivery 3.0, PPS, and Quick Charge 3.0 & 4+ compatibility, enjoy super-fast, optimal charging.

The built-in output display shows real-time wattage and charging status, keeping you informed. Ideal for travel, it includes foldable US prongs, EU/UK plugs, and features flame-resistant polycarbonate construction.

Comes in eco-friendly packaging with a 2-year warranty.



PPS  
Support



Charge  
3 Devices



Multi-Plug  
Included



Retractable  
USB-C Cable



General Information			
Approx. product dimensions LxWxH	58.5 x 50 x 50 mm		
Product weight	157 g		
Product material	PC flame retardant material V0		
Colour	Black		
Input Plug Formats	US (Type A) / EU (Type C) / UK (Type G)		
Supported devices	Laptop, iPhone, iPad, Smartphones, Tablet PCs, MP3/MP4 players, smartwatch, etc.		
RoHS REACH	Yes		
Certifications	CE/LVD/FCC/CB		
Power			
Input	100-240 V AC 50/60Hz 2.8A (Max)		
Total Output	65W Max		
Charging mode	USB-C: PPS/PD3.0/ ,QC4+QC3.0/QC2.0, AFC,FCP,SCP, Apple 2.4A USB-A: QC3.0, QC2.0, AFC, FCP, SCP, Apple 2.4A		
Single Port Output			
USB-C cable Output	5V/3A,9V/3A,12V/3A,15V/3A,20V/3.25A; PPS:5-11V/4.5A		
USB-C Output	5V/3A,9V/3A,12V/3A,15V/3A,20V/3.25A; PPS:5-11V/4.5A		
USB-A Output	5V/3A, 9V/3A, 12V/3A, 20V/3A		
Multiport Output	USB-C1 PD 3.0	USB-C2 PD 3.0	USB-A QC 3.0
USB-C1+USB-C2	45W Max	20W Max	-
USB-C1+USB-A	45W Max	-	18 Watt Max
USB-C2+USB-A	-	15 W Max	-
USB-C1+USB-C2+USB-A	45W Max	15 W Max	-



US  
Type A



UK  
Type G



EU  
Type C

## Safety

Output short circuit protect	Yes
Over-voltage protection	Yes
Over-current protection	Yes
Over-temperature protection	Yes

## Directives

Electromagnetic compatibility	2014/30/EC
Low voltage protection	2014/35/EC
General product safety	2001/95/EC
RoHS directive	2011/65/EC
Annex II	2015/863/EC
Test standards	EN 55032:2015+A11:2020+A1:2020 EN 55035:2017+A11:2020 EN 61000-3-2:2019+A2021 EN 61000-3-3:2013+A1:2019+A2:2021 EN IEC 62386-1:2020+A11:2020

## Storage and Operating Conditions

Storage temperature	-20°C to +80°C
Operating temperature	-10°C to +40°C
Operating humidity	5%(0°)-90%(40°)RH

PN	Description	Tariff Code	Bar Code	EAN128 Code	EAN14 Code
32217	Verbatim GaN Charger 65W 2 Port retractable cable display US plugs with EU and UK adaptors	85366990	23942322177	(02)00023942322177(37)10(91)892 (02)00023942322177(37)20(91)892	20023942322171 50023942322172

## Logistic Information

Product Dimensions: L x W x H	58.5 x 50 x 50 mm
Product Weight:	157 g
Units per Pack:	1
Pack Dimensions:	110 x 53 x 123 mm
Pack Weight:	255 g
Packs per Inner Carton:	10
Inner Carton Dimensions: L x W x H	285 x 265 x 130 mm
Inner Carton Weight:	2900 g
Packs per Outer Carton:	20
Outer Carton Dimensions: L x W x H	300 x 280 x 290 mm
Outer Carton Weight:	6550 g
Outer Cartons per Layer:	16
Layers per Pallet:	4
Units per Pallet:	1280



## Pack Contents

- Verbatim GaN Charger
- EU and UK plug Adapter
- Quick Start Guide



INDOOR USE ONLY.

## Warranty

2 year limited warranty

For more information, please contact your key account manager

Publication date: 18/11/2024  
© 2024 Verbatim. All rights reserved.  
All brand names are registered trademarks of their respective owners.  
Unauthorized use strictly prohibited.  
Specifications are subject to change without prior notice.

